



 ODU-MAC® Blue-Line	 ODU-MAC® White-Line	 ODU-MAC® Silver-Line	 ODU DOCK Silver-Line	 ODU-MAC® Power Connector
PE	25 mm <sup>2</sup>	25 mm <sup>2</sup>	25 mm <sup>2</sup>		70mm <sup>2</sup>
UV	4 kV / 1 mm <sup>2</sup>	6.3 kV / 0.25 mm <sup>2</sup>	6.3 kV / 0.25 mm <sup>2</sup>	2.5 kV / 1.5 mm <sup>2</sup>	4 kV / 1 mm <sup>2</sup>
HF	12 GHz	9 GHz	9 GHz	9 GHz	12 GHz
Temp	-0,8°C	-0,8°C	-0,8°C	-0,8°C	-0,8°C
Pressure	1.0 MPa	2.5 MPa	2.5 MPa	1.0 MPa	1.0 MPa
POF / GOF	PC / APC / Expanded Beam	PC / APC / Expanded Beam / Expanded Beam Performance	PC / APC / Expanded Beam / Expanded Beam Performance		PC / APC / Expanded Beam
Connectivity	SPE / CAT 6A1 / USB®1 / HDMI®1 / DisplayPort	SPE / CAT 6A1 / USB®1 / HDMI®1 / DisplayPort	SPE / CAT 6A1 / USB®1 / HDMI®1 / DisplayPort	SPE / CAT 6A1 / USB®1	SPE / CAT 6 <sub>A</sub> / USB® / HDMI® / DisplayPort
Length	20m	20m	20m		20m
Weight					
Dimensions	K00T0 / 0.5mm <sup>2</sup>	K00T0 / 0.5mm <sup>2</sup>	K00T0 / 0.5mm <sup>2</sup>	K00T0 / 0.5mm <sup>2</sup>	K00T0 / 0.5mm <sup>2</sup>