




ODU LAMTAC®



ODU SPRINGTAC®



ODU SPRINGTAC® 0.64mm pitch



ODU TURNTAC®


Series	ODU LAMTAC®	ODU SPRINGTAC®	ODU SPRINGTAC® 0.64mm pitch	ODU TURNTAC®
Material	Aluminum	Aluminum	Aluminum	Aluminum
Material finish	Aluminum	Aluminum	Aluminum	Aluminum
Number of positions	19 positions (0.6mm pitch)	44 positions (0.6mm pitch)	30 positions (0.63 x 0.8mm pitch)	40 positions (0.6mm pitch)
Current	115 A (0.6mm pitch)	110 A (0.6mm pitch)	27 A (0.63 x 0.8mm pitch)	100 A (0.6mm pitch)
Insertion angle	+/- 1°	+/- 1°		+/- 5°*
Number of pins	10 pins	10 pins	50 pins	10 pins
Temperature range	-40°C to 150°C	-40°C to 125°C	-40°C to 125°C	-40°C to 125°C
Pin diameter	Ø 1.5mm	Ø 0.76mm	Ø 0.64 x 0.64mm	Ø 1.5mm
Pin length	10mm	10mm	10mm	10mm
Pin diameter	•	•	•	•
Pin diameter	•	•	•	•



ODU LAMTAC®



ODU SPRINGTAC®



ODU SPRINGTAC® □□□□□□□□



ODU TURNTAC®

●

●

●***

[illegible]
