ODU CONNECTORS – TECHNICAL DATA

	 ODU LAMTAC®	 ODU SPRINGTAC®	 ODU SPRINGTAC® [illegible]	 ODU TURNTAC®
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	19[illegible]6mm[illegible]	44[illegible]6 mm[illegible]	30[illegible]6.3 x 0.8 mm[illegible]	4[illegible]6[illegible]
[illegible]	115 A[illegible]6 mm[illegible]	110 A[illegible]6 mm[illegible]	27 A ([illegible]6.3 x 0.8 mm)	100 A[illegible]6 mm[illegible]
[illegible]	+/- 1°	+/- 1°		+/- 5° *
[illegible]	1[illegible]	10[illegible]	5[illegible]	1[illegible]
[illegible]	-40[illegible]150[illegible]	-40[illegible]125[illegible]	-40[illegible]125[illegible]	-40[illegible]125[illegible]
[illegible]	∅ 1.5mm[illegible]	∅ 0.76mm[illegible]	∅ 0.64 x 0.64 mm[illegible]	∅ 1.5mm[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	●	●	●	●
[illegible]	●	●	●	●

	 ODU LAMTAC®	 ODU SPRINGTAC®	 ODU SPRINGTAC® [illegible]	 ODU TURNTAC®
[illegible]	•	•		•***

*[illegible]5[illegible]

**[illegible]

***[illegible]