





ODU LAMTAC®



ODU SPRINGTAC®



ODU SPRINGTAC®




ODU TURNTAC®


	ODU LAMTAC®	ODU SPRINGTAC®	ODU SPRINGTAC®	ODU TURNTAC®
Series	ODU LAMTAC	ODU SPRINGTAC	ODU SPRINGTAC	ODU TURNTAC
Material	Aluminum	Aluminum	Aluminum	Aluminum
Dimensions	19mm length, 6mm diameter	44mm length, 6mm diameter	30mm length, 6.3 x 0.8 mm	40mm length, 6mm diameter
Current Rating	115 A (6mm diameter)	110 A (6mm diameter)	27 A (6.3 x 0.8 mm)	100 A (6mm diameter)
Angle	+/- 1°	+/- 1°		+/- 5°*
Temperature Range	100°C	100°C	50°C	100°C
Storage Temperature	-40°C to 150°C	-40°C to 125°C	-40°C to 125°C	-40°C to 125°C
Wire Size	Ø 1.5mm	Ø 0.76mm	Ø 0.64 x 0.64 mm	Ø 1.5mm
Material	Aluminum	Aluminum	Aluminum	Aluminum
Material	Aluminum	Aluminum	Aluminum	Aluminum
Material	Aluminum	Aluminum	Aluminum	Aluminum



ODU LAMTAC®



ODU SPRINGTAC®



ODU SPRINGTAC® 00000000



ODU TURNTAC®

000000
000000
00

•

•

•***

*00000000000000000000000000000050

**000000000000

***00000000