

	 ODU AMC®	 ODU AMC® Easy-Clean	 ODU AMC® High-Density	 ODU AMC® Threaded	 ODU AMC® □□□ T	 ODU AMC® NP
IP □ □ □ □ □	□ □ IP6K9K	□ □ IP6K9K	□ □ IP6K9K	□ □ IP6K8	□ □ IP6K8	IP68
IP □ □ □ □ □ □ □	IP68	IP6K8	IP68	IP68	IP68	IP68(□□□□ □ □ □ □ □ □)
□ □	□ □ □	□ □ □	□ □ □	□ □ □	□ □ □	□ □ □
□ □ □ □ □	> 5.000	> 5.000	> 5.000	> 2.000	> 500	> 2.000
□ □ □ □	□ □, PCB	□ □, PCB	□ □, PCB	□ □, PCB	□ □, □ □ □, PCB	□ □, PCB
□ □ □	□ □ □ □	□ □ □ □	□ □	□ □ □ □	□ □ □ □	□ □ □ □
□ □	□ □ □	□ □ □	□ □ □	□ □ □ □	□ □ □ □	RoHS □ □ □ □
□ □ □ □ □ □	-51 °C ~ +125 °C	-51 °C ~ +125 °C	-51 °C ~ +125 °C	-51 °C ~ +125 °C	-65 °C ~ +175 °C	-18 °C ~ +71 °C